

## SELF-LEVELLING FIVE-BEAM LASER POINTERS

- Simultaneously projects five self-levelling beams
- Alarm when unit is beyond accurate range
- Low power indicator
- Locking mechanism protects unit in transport
- Includes: Laser level, multifunction mount, three AA batteries, tinted glasses, magnetic target, strap and carrying case



### TECHNICAL SPECIFICATIONS

<b>Model No.</b>	<b>TGZ560</b>
<b>Mfg. No.</b>	40-6680
<b>Laser wave length:</b>	635 nm ± 10 nm
<b>Laser classification:</b>	Class 111A
<b>Accuracy:</b>	± 1/4" @ 100' (± 2 mm @ 10 m)
<b>Working range:</b>	Max. 100' (30 m) depending on light conditions
<b>Working temperature:</b>	14°F to 113°F (-10°C to 40°C)
<b>Price/Each</b>	\$

## ELECTRONIC SELF-LEVELLING ROTARY LASER KIT



- Designed for indoor and outdoor applications
- Electronically-controlled dual slope feature
- Electronic self-leveling horizontally and vertically
- Laser beam modes include four adjustable line lengths and three rotational speeds
- Three rotational speeds—0, 300 and 800 RPM
- Visual and audible alarms when beyond leveling range
- Height of Instrument/Tilt alarm function ensures product accuracy
- Includes: Laser, Li-ion rechargeable battery pack, Alkaline battery compartment (batteries not included), Li-ion battery charger, Remote control with 9V battery, Detector with 9V battery and clamp, Tinted glasses, and Hard-shell carrying case
- Max. Power Output: Less than/Equal to 5 mW
- Power Supply: Li-ion rechargeable battery pack or adapter (included); 3 "C" alkaline batteries (not included)



### TECHNICAL SPECIFICATIONS

<b>Model No.</b>	<b>IB884</b>
<b>Mfg. No.</b>	40-6522
<b>Laser wave length:</b>	635 nm
<b>Laser classification:</b>	Class IIIA
<b>Interior Range:</b>	Up to 200 ft. (60m) diameter depending on light conditions
<b>Exterior Range:</b>	Up to 2000 ft. (610m) diameter with detector
<b>Remote Range:</b>	Up to 200 ft. (60m) diameter with remote
<b>Slope:</b>	+/- 5 degrees
<b>Auto-Leveling Range:</b>	+/- 5 degrees
<b>Working temperature:</b>	-10°C to +45°C
<b>Price/Each</b>	\$

## MANUAL-LEVELING ROTARY LASER LEVELS

- Emits horizontal or vertical laser plane with simultaneous 90° split beam
- Large and small scan modes achieve a chalk line
- Scan line can be moved clockwise or counter-clockwise
- Includes: Manual-leveling rotary laser level, 4 x AA alkaline batteries, wall/ceiling mount, 8' grade rod, detector with 2 x AAA batteries and clamp, tinted glasses, magnetic target, elevating tripod, instruction manual with warranty card, hard-shell carrying case
- Variable rotation speed



### TECHNICAL SPECIFICATIONS

<b>Model No.</b>	<b>TLV309</b>
<b>Mfg. No.</b>	40-6512
<b>Laser wave length:</b>	635 nm ± 10 nm
<b>Laser classification:</b>	Class 111A
<b>Accuracy:</b>	+/-1/4"/100' (+/-2 mm/10 m)
<b>Max. working range:</b>	Up to 800' diameter (240 m) with detector
<b>Working temperature:</b>	14°F to 113°F (-10-45°C)
<b>Price/Each</b>	\$

## 3 BEAM SELF-LEVELLING LINE LASER

- 3 Beam Line Laser to aid in 90° layout
- 2x Brighter diode to increase visibility in bright job site conditions
- Built-in magnetic pivot bracket mounts easily on metal surfaces
- 1-button operation and control panel for ease of use
- Micro adjust knob for precise alignment of 90° intersecting lines over greater distances
- Includes: 4 AA batteries for 30 hours of run-time, Ceiling Mount and Kit Box



### TECHNICAL SPECIFICATIONS

<b>Model No.</b>	<b>TMB038</b>
<b>Mfg. No.</b>	DW089K
<b>Accuracy:</b>	±1/8" @ 30'
<b>Power:</b>	6 V, 4-AA Battery
<b>Run Time:</b>	30 hours
<b>Price/Each</b>	\$