

# HACKSAWS & ACCESSORIES



## CUSHION GRIP HACKSAW FRAMES

- Unique cushioned rubber grip reduces slippage for better control and comfort
- Rugged, sturdy frame built for professional tool users
- High tension technology for tightening the blade to 30,000 PSI
- Blade can be positioned for 45° or 90° cutting
- Patented quick change blade design

**Model No. TJ246**  
**Mfg. No. 80965**  
**Price/Each \$**



**CRESCENT NICHOLSON**

## HIGH TENSION HACKSAW FRAMES

- Quick changing blades
- Adjustable crank handle for tension up to 30,000 PSI torque and micro-adjustment
- Spare blades can be stored inside frame
- Blade can be positioned for 45° or 90° cutting
- End of frame can be used as a jab saw

**Model No. TJ557**  
**Mfg. No. 80956**  
**Price/Each \$**



**CRESCENT NICHOLSON**

## HEAVY-DUTY HACKSAW FRAMES

- High impact, contoured handle
- Adjust to 10" or 12"
- 45° blade adjustment

**Model No. TBH296**  
**Mfg. No. 80952**  
**Price/Each \$**



**CRESCENT NICHOLSON**

## ECONOMY HACKSAW FRAMES

- Adjustable from 10"/250 mm to 12"/300 mm
- Cuts to 2.75"/70 mm in depth
- For DIY and home use

**Model No. TJ251**  
**Mfg. No. 80950**  
**Price/Each \$**



**CRESCENT NICHOLSON**

## GENERAL PURPOSE HACKSAW FRAMES

- Instantly adjustable for 10"/250 mm to 12"/300 mm blades
- Adjusts 90° for vertical or horizontal cuts

**Model No. VU145**  
**Mfg. No. 80951**  
**Price/Each \$**



**CRESCENT NICHOLSON**

## HACKSAWS

- Blade Length: 12"
- Handle Type: Plain
- Overall Dimensions: 17-5/16" L x 5-1/8" H
- Depth of Bow: 4" H
- Tensile Strength: 8000 PSI
- Strong aluminum die-cast handle provides comfort and control
- Guarded grip design protects knuckles from grazing

**Model No. TYW991**  
**Price/Each \$**



**aurora tools®**

## HIGH TENSION HACKSAW FRAMES

- Professional quality high tension frame provides easy to use an efficient adjustment lever
- Rubber handle and thumb hold provides an ergonomic grip (**EAM042**)
- 4 angled mounting pins allow for both straight and angle cutting, also keeps the blade in place when tension is relieved
- Blade tension is approximately 28 000 PSI (2000 kg/cm<sup>2</sup>)
- To tension blade, make 3 turn (360°) after first meeting resistance with blade
- Model **EAM042** comes with a Starrett Bluestripe bi-metal unique® ground tooth hacksaw blade, model **TBD490** comes with a Starrett Greenstripe® bi-metal unique® milled tooth hacksaw blade



**TBD490**



**EAM042**

**Starrett®**

## LITTLE-NIC® UTILITY HACKSAWS

- Ergonomic cushioned handle
- Gets into small places
- Overall length 10"/250 mm,
- Uses any standard size hacksaw blade

**Model No. TBH298**  
**Mfg. No. 80968**  
**Price/Each \$**



**CRESCENT NICHOLSON**

## JAB SAWS

- Special saw always needed for the difficult jobs: those narrow, hard-to-read areas
- Jab saw will work with any standard size hacksaw blade
- Can replace worn blade easily

**Model No. TJ252**  
**Mfg. No. 80969**  
**Price/Each \$**



**CRESCENT NICHOLSON**

| Model No.     | Mfg. No. | Description   | Throat Depth   | Price /Each |
|---------------|----------|---|----------------|-------------|
| <b>EAM042</b> | 67818    | 12" closed grip heavy-duty high tension hacksaw frame | 4 3/8" (110mm) |             |
| <b>TBD490</b> | 60134    | Heavy-duty adjustable closed grip hacksaw frame       | 3 3/4" (95mm)  |             |